

00560-020 CONNECTOR

SUGGESTED SET-UP VALUES

The following tables are suggested ways of arriving at required load values. There are usually several options other than those shown below. The five pin locations are designated as A, B, C, D & E. (See Diagram).


BREAKLOAD - LB

Pin Location (See Location Reference Diagram)					Break Value
A	B	C	D	E	lb.
-	-	-	-	3,000	3,000
6,000	-	6,000	-	-	12,000
3,000	-	3,000	-	7,000	13,000
7,000	-	7,000	-	-	14,000
3,000	-	3,000	-	9,000	15,000
8,000	-	8,000	-	-	16,000
7,000	-	7,000	-	3,000	17,000
9,000	-	9,000	-	-	18,000
8,000	-	8,000	-	3,000	19,000
7,000	-	7,000	-	6,000	20,000
7,000	-	7,000	-	7,000	21,000
7,000	-	7,000	-	8,000	22,000
7,000	-	7,000	-	9,000	23,000
8,000	-	8,000	-	8,000	24,000
8,000	-	8,000	-	9,000	25,000
9,000	-	9,000	-	8,000	26,000
9,000	-	9,000	-	9,000	27,000
7,000	7,000	7,000	7,000	-	28,000
3,000	7,000	3,000	7,000	9,000	29,000
6,000	6,000	6,000	6,000	6,000	30,000
6,000	6,000	6,000	6,000	7,000	31,000
6,000	6,000	6,000	6,000	8,000	32,000
6,000	6,000	6,000	6,000	9,000	33,000
7,000	7,000	7,000	7,000	6,000	34,000
7,000	7,000	7,000	7,000	7,000	35,000
7,000	7,000	7,000	7,000	8,000	36,000
7,000	7,000	7,000	7,000	9,000	37,000
8,000	7,000	8,000	7,000	8,000	38,000
8,000	7,000	8,000	7,000	9,000	39,000
8,000	8,000	8,000	8,000	8,000	40,000
8,000	8,000	8,000	8,000	9,000	41,000
9,000	9,000	9,000	9,000	6,000	42,000
9,000	9,000	9,000	9,000	7,000	43,000
9,000	9,000	9,000	9,000	8,000	44,000
9,000	9,000	9,000	9,000	9,000	45,000

BREAKLOAD - KG

Pin Location (See Location Reference Diagram)					Break Value
A	B	C	D	E	kg.
-	-	-	-	3,000	3,000
3,000	-	3,000	-	-	6,000
2,000	-	2,000	-	2,500	6,500
2,000	-	2,000	-	3,000	7,000
2,000	-	2,000	-	3,500	7,500
4,000	-	4,000	-	-	8,000
3,000	-	3,000	-	2,500	8,500
3,000	-	3,000	-	3,000	9,000
3,000	-	3,000	-	3,500	9,500
3,000	-	3,000	-	4,000	10,000
4,000	-	4,000	-	2,500	10,500
4,000	-	4,000	-	3,000	11,000
4,000	-	4,000	-	3,500	11,500
4,000	-	4,000	-	4,000	12,000
2,500	2,500	2,500	2,500	2,500	12,500
2,500	2,500	2,500	2,500	3,000	13,000
2,500	2,500	2,500	2,500	3,500	13,500
2,500	2,500	2,500	2,500	4,000	14,000
3,000	3,000	3,000	3,000	2,500	14,500
3,000	3,000	3,000	3,000	3,000	15,000
3,000	3,000	3,000	3,000	3,500	15,500
3,000	3,000	3,000	3,000	4,000	16,000
3,000	3,500	3,000	3,500	3,500	16,500
3,500	3,500	3,500	3,500	3,000	17,000
3,500	3,500	3,500	3,500	3,500	17,500
3,500	3,500	3,500	3,500	4,000	18,000
4,000	3,500	4,000	3,500	3,500	18,500
4,000	3,500	4,000	3,500	4,000	19,000
4,000	4,000	4,000	4,000	3,500	19,500
4,000	4,000	4,000	4,000	4,000	20,000

*Note: Uneven pin distribution may result in up to 10% higher breaking point.



PIN LOCATION REFERENCE

Website: www.dcdesign.com

Toll Free: 1-888-SWIVELS (794-8357)

Tel: 604-232-4445

Fax: 604-232-4446

E-mail: sales@dcdesign.com

